
# CABLES

POLYCAB







# LT XLPE CABLE

**TDS Doc.No:PIL/TE/250425/001336**

**DESIGN CODE : LVIS09AXSFY2002C300SA001S**

| Particulars | | 2 Core X 300 Sq.mm |
|---|---|---|
| Name of Manufacturer | | Polycab India Ltd |
| Type of cable | | A2XFY |
| Voltage Grade V | | 1100 |
| No of cores X size in sqmm | | 2 Core X 300 Sq.mm |
| **Conductor** | | |
| a) | Material | H2/H4 Grade Aluminium as per Class 2 of IS: 8130/2013,latest |
| b) | Max. d.c. resistance of conductor at 20° C (ohm/km) | 0.100 |
| c) | Shape of the conductor | Stranded Compacted Sector |
| **Insulation** | | |
| a) | Material | XLPE as per IS 7098(Pt-1)/88, Latest |
| b) | Nominal thickness (mm) | 1.8 |
| c) | Core identification | Red,Black |
| **Inner Sheath** | | |
| a) | Material | Extruded PVC Type ST2 as per IS:5831/84 |
| b) | Minimum thickness (mm) | 0.6 |
| **Armouring** | | |
| a) | Material | Galvanised Steel |
| b) | Type of armouring | Flat Strip |
| c) | Nominal size of armour (mm) | 4.0 x 0.8 |
| d) | Tolerance on armour dimensions | ± 10% |
| **Outer Sheath** | | |
| a) | Material | Extruded PVC Type 'ST2' as per IS:5831/84 |
| b) | Thickness (mm) | 2.04 (Min.) |
| c) | Colour of sheath | Black |
| **Electrical Parameters** | | |
| a) | Max. a.c. resistance of conductor at 90° C (ohm/km) | 0.130 |

Format ID: TE/QMS/F/07, R-00, Date: 16/03/2025

| | | |
|---|---|---|
| b) | Calculated Cable reactance (ohm/km) | 0.0703 |
| c) | Impedance of cable (ohm/km) | 0.148 |
| d | Approx. Cable Capacitance (mfd/km) | 0.71 |
| Maximum conductor temperature under normal operating conditions | | 90°C |
| Maximum conductor temperature at the termination of short circuit | | 250°C |
| Short Circuit rating of conductor for the duration of 1 sec (kA) | | 28.35 |
| **Continuous Current carrying capacities :-** | | |
| (a) | In Ground at 30°C (A) | 432 |
| (b) | In Air at 40°C (A) | 513 |
| Applicable Standard | | IS 7098 Part I/88,IS 8130/2013,IS 5831/84, IS 3975/1999 etc. with latest up to date amendments |
| Approx. overall diameter of the cable in mm | | 45.0 ± 2.0 |
| Minimum bending radius | | 12 times Overall diameter |
| Max. Tensile strength | | |
| (i) | for Cables pulled with stocking (Newtons) | 9 x $D^2$, D is the cable OD in mm |
| (ii) | for Cables pulled with pulling eyes (N) | 18,000 |
| Embossing | | POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE |
| Printing | | YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval. |
| Standard Drum Length (Mtr.) | | 500 ± 5% |
| Non- Standard Drum Length (Mtr.) | | Maximum 5% of order quantity |



Note:-The values given above are subject to tolerances as per the relevant standards