
POLYCAB

CABLES





LT XLPE CABLE

TDS Doc.No:PIL/TE/250425/000017

DESIGN CODE: LVIS09CXSWY2002C004SA002S

Particulars	**2 Core X 4 Sq.mm**
Name of Manufacturer	Polycab India Ltd
Type of cable	2XWY
Voltage Grade V	1100
No of cores X size in sqmm	2 Core X 4 Sq.mm
Conductor	
a) Material	Plain annealed Copper as per Class 1 of IS:8130/2013, latest
b) Max. D.C. resistance of conductor at 20° C (ohm/km)	4.61
c) Shape of the conductor	Solid Circular
Insulation	
a) Material	XLPE as per IS 7098(Pt-1)/88, Latest
b) Nominal thickness (mm)	0.7
c) Core identification	Red, Black
Inner Sheath	
a) Material	Extruded PVC Type ST2 as per IS:5831/84
b) Minimum thickness (mm)	0.3
Armouring	
a) Material	Galvanised Steel
b) Type of armouring	Round Wire
c) Nominal size of armour (mm)	1.4
d) Tolerance on armour dimensions	± 0.040 mm
Outer Sheath	
a) Material	Extruded PVC Type 'ST2' as per IS:5831
b) Thickness (mm)	1.24 (Min.)
c) Colour of outer sheath.	Black
Electrical Parameters	
a) Max. a.c. resistance of conductor at 90° C (ohm/km)	5.88
b) Calculated Cable reactance (ohm/km)	0.0919
c) Impedance of cable (ohm/km)	5.88

Rev.No.:00 **Issued Date:02/04/2018**

Note: -The values given above are subject to tolerances as per the relevant standards.

Format ID: TE/QMS/F/07, R-00, Date: 16/03/2025

d) Approx. Cable Capacitance (mfd/km)	0.23
Maximum conductor temperature under normal operating conditions	90°C
Maximum conductor temperature at the termination of short circuit	250°C
Short Circuit rating of conductor for the duration of 1 sec (kA)	0.57
Continuous Current carrying capacities :-	
a) In Ground at 30°C (A)	54
b) In Air at 40°C (A)	48
Applicable Standard	IS 7098 Part I/88,IS 8130/2013,IS 5831/84, IS 3975/1999 etc. with latest up to date amendments
Approx. overall diameter of the cable in mm	13.5 ± 2.0
Minimum bending radius	12 times Overall diameter
Max. Tensile strength	
i) for Cables pulled with stocking (Newtons)	9 x D^2, D is the cable OD in mm
ii) for Cables pulled with pulling eyes (N)	400
Embossing	POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every onemeter interval.
Printing	
Standard Drum Length (Mtr.)	1000 ± 5%
Non- Standard Drum Length (Mtr.)	Maximum 5% of order quantity

Note:-The values given above are subject to tolerances as per the relevant standards