
POLYCAB

# CABLES







# LT XLPE CABLE

**TDS Doc.No:PIL/TE/250425/002771**

**DESIGN CODE : LVIS09CXSWY2002C2.5SA002S**

| Particulars | | 2 Core X 2.5 Sq.mm |
|---|---|---|
| Name of Manufacturer | | Polycab India Ltd. |
| Type of cable | | 2XWY |
| Voltage Grade V | | 1100 |
| No of cores X size in sqmm | | 2 Core X 2.5 Sq.mm |
| **Conductor** | | |
| a) | Material | Plain annealed Copper as per Class 1 of IS:8130/2013 |
| b) | Max. d.c. resistance of conductor at 20° C (ohm/km) | 7.4100 |
| c) | Shape of the conductor | Solid Circular |
| **Insulation** | | |
| a) | Material | XLPE as per IS 7098(Pt-1)/88, Latest |
| b) | Nominal thickness (mm) | 0.7 |
| c) | Core Identification | Red,Black |
| **Inner Sheath** | | |
| a) | Material | Extruded PVC Type ST2 as per IS:5831/84 |
| b) | Minimum thickness (mm) | 0.3 |
| **Armouring** | | |
| a) | Material | Galvanised Steel |
| b) | Type of armouring | Round Wire |
| c) | Nominal size of armour (mm) | 1.400 |
| d) | Tolerance | +/- 0.040 |
| **Outer Sheath** | | |
| a) | Material | Extruded PVC Type ST2 as per IS:5831/84 |
| b) | Thickness (mm) | 1.24 (Min.) |
| c) | Colour of outer sheath. | Black |
| **Electrical Parameters** | | |
| a) | Max. a.c. resistance of conductor at 90° C (ohm/km) | 9.4500 |
| b) | Calculated Cable reactance (ohm/km) | 0.0983 |

Format ID: TE/QMS/F/07, R-00, Date: 16/03/2025

| | | |
|---|---|---|
| c) | Impedance of cable (ohm/km) | 9.4500 |
| d | Approx. Cable Capacitance (mfd/km) | 0.19 |
| Maximum conductor temperature under normal operating conditions | | 90°C |
| Maximum conductor temperature at the termination of short circuit | | 250°C |
| Short Circuit rating of conductor for the duration of 1 sec (kA) | | 0.36 |
| **Continuous Current carrying capacities :-** | | |
| (a) | In Ground at 30°C (A) | 41 |
| (b) | In Air at 40°C (A) | 36 |
| Applicable Standard | | IS 8130/2013,IS 7098 Part I/88, IS 5831/84, IS 3975/1999 etc. with latest up to date amendments |
| Approx. overall diameter of the cable in mm | | 13.0 +/- 2.0 |
| Minimum bending radius | | 12 times Overall diameter |
| Max. Tensile strength | | |
| (i) | for Cables pulled with stocking (Newtons) | 9 x $D^2$, D is the cable OD in mm |
| (ii) | for Cables pulled with pulling eyes (N) | 250 |
| Embossing | | POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE |
| Printing | | YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval. |
| Standard Drum Length (Mtr.) | | 1000 ± 5% |
| Non- Standard Drum Length (Mtr.) | | Maximum 5% of order quantity |



Note:-The values given above are subject to tolerances as per the relevant standards