
CABLES

POLYCAB





LT XLPE CABLE

TDS Doc.No:PIL/TE/250425/001129 **DESIGN CODE : LVIS09CXUAY23.5C185SA001S**

Particulars		3.5 Core X 185 Sq.mm
Name of Manufacturer		Polycab India Ltd
Type of cable		2XY
Voltage Grade V		1100
No of cores X size in sqmm		3.5 Core X 185 Sq.mm
Conductor		
a) Material		Plain annealed Copper as per Class 2 of IS:8130/2013, latest
b) Max. d.c. resistance of conductor at 20° C (ohm/km)	Main	0.0991
	Neutral	0.193
c) Shape of the conductor		Stranded Compacted Sector
Insulation		
a) Material		XLPE as per IS 7098(Pt-1)/88, Latest
b) Nominal thickness (mm)	Main	1.6
	Neutral	1.1
c) Core identification		Red,Yellow,Blue,Black
Inner Sheath		
a) Material		Extruded PVC Type ST2 as per IS:5831/84
b) Minimum thickness (mm)		0.5
Outer Sheath		
a) Material		Extruded PVC Type 'ST2' as per IS:5831
b) Thickness (mm)		2.6 (Nom.)
c) Colour of outer sheath.		Black
Electrical Parameters		
a) Max. a.c. resistance of conductor at 90° C (ohm/km)		0.128
b) Calculated Cable reactance (ohm/km)		0.0720
c) Impedance of cable (ohm/km)		0.147
d Approx. Cable Capacitance (mfd/km)		0.00
Maximum conductor temperature under normal operating conditions		90°C

Format ID: TE/QMS/F/07, R-00, Date: 16/03/2025

POLYCAB

Maximum conductor temperature at the termination of short circuit	250°C
Short Circuit rating of conductor for the duration of 1 sec (kA)	26.47
Continuous Current carrying capacities :-	
(a) In Ground at 30°C (A)	362
(b) In Air at 40°C (A)	422
Applicable Standard	IS 7098 Part I/88, IS 8130, IS 5831 etc. with latest up to date amendments
Approx. overall diameter of the cable in mm	47.0 ± 2.0
Minimum bending radius	12 times Overall diameter
Max. Tensile strength	
(i) for Cables pulled with stocking (Newtons)	5 x D^2, D is the cable OD in mm
ii) for Cables pulled with pulling eyes (N)	32,500
Embossing	POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE
Printing	YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval.
Standard Drum Length (Mtr.)	500 ± 5%
Non- Standard Drum Length (Mtr.)	Maximum 5% of order quantity

Note:-The values given above are subject to tolerances as per the relevant standards