
POLYCAB

CABLES





LT XLPE CABLE

TDS Doc.No:PIL/TE/250425/002831

DESIGN CODE : LVIS09CXUAYL012C2.5SA001S

Particulars	12 Core X 2.5 Sq.mm
Name of Manufacturer	Polycab India Ltd.
Type of cable	2XY
Voltage Grade V	1100
No of cores X size in sqmm	12 Core X 2.5 Sq.mm
Conductor	
a) Material	Plain annealed Copper as per Class 1 of IS:8130/2013
b) Max. d.c. resistance of conductor at 20° C (ohm/km)	7.41
c) Shape of the conductor	Solid Circular
Insulation	
a) Material	XLPE as per IS 7098(Pt-1)/88, Latest
b) Nominal thickness (mm)	0.7
c) Core Identification	All cores Grey with number printing
Inner Sheath	
a) Material	Extruded PVC Type ST2 as per IS:5831/84
b) Minimum thickness (mm)	0.3
Armouring	Not Applicable
Outer Sheath	
a) Material	Extruded FR-LSH PVC Type ST2 as per IS:5831/84
b) Thickness (mm)	1.8 (Nom.)
c) Colour of outer sheath.	Black
Electrical Parameters	
a) Max. a.c. resistance of conductor at 90° C (ohm/km)	9.5
b) Calculated Cable reactance (ohm/km)	0.098
c) Impedance of cable (ohm/km)	9.5
Maximum conductor temperature under normal operating conditions	90°C
Maximum conductor temperature at the termination of short circuit	250°C

Format ID: TE/QMS/F/07, R-00, Date: 16/03/2025

Short Circuit rating of conductor for the duration of 1 sec (kA)		0.36
Continuous Current carrying capacities :-		
(a)	In Ground at 30°C (A)	20
(b)	In Air at 40°C (A)	18
Applicable Standard		IS 8130/2013,IS 7098 Part I/88, IS 5831/84, IS 3975/1999 etc. with latest up to date amendments
Approx. overall diameter of the cable in mm		18.0 ± 2.0
Minimum bending radius		12 times Overall diameter
Max. Tensile strength		
(i)	for Cables pulled with stocking (Newtons)	5 x D^2, D is the cable OD in mm
(ii)	for Cables pulled with pulling eyes (N)	1500
Embossing		POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR-LSH
Printing		YEAR POLYCAB ELECTRIC 1100 VOLTS GRADE XLPE FR-LSH CABLE SIZE CABLE TYPE WITH SEQUENTIAL MARKING at every one meter interval.
Standard Drum Length (Mtr.)		1000 ± 5%
Non- Standard Drum Length (Mtr.)		Maximum 5% of order quantity
PROPERTIES		
a)	Oxygen Index	Min. 29% as per ASTM D- 2863
b)	Temperature Index	Min. 250 Deg.C as per ASTM D- 2863
c)	Smoke Density Rating	Max. 60% as per ASTM D- 2843
d)	Acid Gas Generation	Max. 20% as per IEC- 754- 1
e)	Flammability Test	As per IEC:332-I

Note:-The values given above are subject to tolerances as per the relevant standards